

Machine Series: ALB

Top and Bottom Labeler



Technical Details:

- equipped with two labeling heads - one for top labeling, the other for bottom labeling (depending on the model)
- stainless high-grade steel construction
- programmable logic controller combined with a touch screen
- highly accurate labeling, ± 1 mm tolerance
- servo-controlled labeling head; labeling speed is automatically synchronized with product throughput speed

Product Samples:



Speed:
Up to 35 m/min



Model:	ALB-210	ALB-210A	ALB-220	ALB-620R	ALB-625
Labeling:	unilateral	unilateral	Simultaneous bilateral	bilateral	bilateral
Label Height/ Width:	A: 10-110 mm C: 10-170 mm*	A: 10-110 mm C: 10-170 mm*	A: 10-110 mm C: 10-170 mm*	A: 10-110 mm C: 10-170 mm*	A: 10-110 mm C: 10-170 mm*
Label Length:	10-250 mm*	10-250 mm*	10-250 mm*	10-250 mm*	10-250 mm*
Product Diameter / Width:	15-160 mm	15-160 mm	15-160 mm	30-100 mm	30-100 mm
Labeling Speed:	12-35 m/min	12-35 m/min	12-35 m/min	12-25 m/min	12-25 m/min
Reel Diameter:	inner 76 mm/ outer 360 mm	inner 76 mm/ outer 360 mm	inner 76 mm/ outer 360 mm	inner 76 mm/ outer 360 mm	inner 76 mm/ outer 360 mm